

PLANK 260 SPECIFICATION SHEET

Atelier Collection Engineered T&G plank by Forté.
21mm thick, 260mm wide, 2200mm length. Glue down
installation method onto substrate. Pre-finished with UV
Cured Matte Lacquer.

PRODUCT DETAILS

Collection	Atelier
Product Type	Engineered Plank
Availability	Stocked
Total Thickness	21mm
Width	260mm
Length	2200mm
% of Shorts	Up to 25%
Wear Layer	6mm Solid European Oak
Core	Eucalyptus Plywood core & backing
Construction	2-layer Engineered
Re-sands	Up to 4 (approx. 1mm removed per re-sand)
Surface Texture	Brushed
Surface Sheen	Matte
Bevel	Bevel Long Edges
Status	Pre-finished (no additional coats required)
Finish	Ageing Stain with UV Cured Matte Lacquer
Species	European Oak
Wood Grade	Rustic (refer page 2 for details)
Filler Colour	Dependant on colour, visit forte.co.nz for accurate filler colour

The Atelier Collection is also available in stair nosings.

STRUCTURAL WARRANTY

10 Year Commercial	For terms and conditions see
25 Year Residential	www.forte.co.nz/warranties



Dolomite

Siltstone

Classic

Marl



Granite

SUSTAINABILITY

Sustainably Sourced

INSTALLATION

Installation Method	Glue down (Double Stick for Multi-level)
Suitable Substrates	Plywood, Particle Board, Concrete, existing timber - enquire for others
Joint Profile	Tongue and Groove (4 sides)
Suitable Applications	Flooring, Walls, Ceilings
Suitable Uses	Residential homes, hospitality, retail stores, restaurants, apartments
Underfloor Heating	<ul style="list-style-type: none"> Hydronic Systems Electric Systems set in screed (Ensure screed is suitable for UFH) Enquire for other systems
Wet Area Suitability	Contact the Forté team for information 0508 35 66 77

TECHNICAL SPECIFICATIONS


Reaction to Fire (Floors)	Critical Flux 2.2kw/m ²
Reaction to Fire (Walls and Ceilings)	Group 3 / Class Dfl-s1 (Group 1 can be achieved with intumescent coating)
Formaldehyde Emission	
AS/NZS 2098.11	E0 (0.13 mg/L) Low VOC, No added Formaldehyde
Wear Layer Density	650kg/m ³
Slip Ratings	
AS/NZS 4586 Wet Test	Classification F, Mean COF 0.85
AS/NZS 4586 Dry Test	Classification X, Pendulum Mean 42 BPN

PACK INFORMATION

Pack Size	2.288m ²
Pack Weight	31.1kg
Pieces per pack	3 full planks + up to 1 split plank

Plank Profile

ATELIER PLANK



ATELIER – RUSTIC GRADE



An Atelier rustic grade plank will typically contain unlimited natural colour variation. This grade allows for more frequent, larger knots and more sapwood should be expected throughout the planks. Cracks and checks will be present and are finished with filler.

Care and Maintenance

RESIDENTIAL AND COMMERCIAL CARE AND MAINTENANCE

Forté's Product Specialists have collated our care and maintenance recommendations to ensure your flooring looks like new for years to come. Residential and Commercial projects require different levels of care and maintenance. Visit www.forte.co.nz/careandmaintenance

Structural Warranty

ATELIER 25 YEAR RESIDENTIAL STRUCTURAL WARRANTY

The Atelier Collection comes with a full 25 year Residential Structural Warranty. For full warranty terms and conditions, please visit www.forte.co.nz/warranties

ATELIER 10 YEAR COMMERCIAL STRUCTURAL WARRANTY

The Atelier Collection comes with a full 10 year Commercial Structural Warranty. For full warranty terms and conditions, please visit www.forte.co.nz/warranties

Installation

THE ATELIER COLLECTION MUST BE INSTALLED BY A TRAINED PROFESSIONAL

Please ensure that you have read and understood the installation guidelines before proceeding to install Atelier timber flooring. If you have any questions or concerns, please call the Forté technical team on 0508 35 66 77. Failure to adhere to the Forté Installation Guidelines may void your warranty.

For full installation guidelines, please visit www.forte.co.nz/installation