
Acoustick-Mat

UNDERLAY SPECIFICATION SHEET





PRODUCT DETAILS

Collection Acoustick-Mat

Product Type Sound Reducing Underlay

CodeAKM10AvailabilityStockedUnit Size10m² RollCoverage10m²Total Thickness5mmWidth1mLength10m

Composition Made from recycled rubber and

cork

Bonding Component Bonded with a waterproof

urethane adhesive

Effectiveness Reduces sound transfer in multi-

level buildings by up to 18dB

SUSTAINABILITY

Made from recycled rubber and cork

INSTALLATION

Installation Method Refer to Acoustick–Mat Acoustic

Underlay Installation Guidelines

Suitable Substrates Plywood, Particle Board, Concrete,

existing timber - Enquire for others

Suitable Applications Commercial or residential buildings

Suitable Uses Multi-level residential homes,

hospitality, retail stores, restaurants,

apartments

Underfloor Heating Not recommended - enquire before

proceeding

Wet Area Suitability Contact the Forté team for information

0508 35 66 77

TECHNICAL SPECIFICATIONS

Density 650kg/m³

Certification Rated according to ISO 717-2:1996
Testing Professionally tested by Marshall Day

Acoustics - Enquire for results

PACK INFORMATION

Pack Size10m²Pieces per pack1 x rollPack Weight35kg

Pack Dimensions H 270mm x W 270mm x L 1020mm

Installation

REFER TO ACOUSTICK-MAT ACOUSTIC UNDERLAY INSTALLATION GUIDELINES

Please ensure that you have read and understood the installation guidelines before proceeding to install Acoustick–Mat If you have any questions or concerns, please call the Forté technical team on 0508 35 66 77. Failure to adhere to the Forté Installation Guidelines may void your warranty. For full installation guidelines, please visit www.forte.co.nz/installation

